



**Thwing-Albert
Instrument Company**

More Than a Century of Testing Solutions

Spectrophotometer RL-SPM-A

Determines the folding resistance of paper, according to the Schopper principle.

The Spectrophotometer is a modern, easy to use and feature rich Color-QC application for paper and packaging industries and automotive supply chain members. It enables customers to analyze, report, communicate and visualize accurate color QC results. It incorporates the indices, tolerance methods, graphs and sight sources D65, C, UV ex. The device either comes with a built in touch screen or can be connected to a PC. The software supports Windows 7 and Windows 8.

The device is easy to control due to its touch screen and the Windows similar use of the program. The dates can be saved into files directly on the computer on in the network. A printer can be connected to the USB port of the device where direct printout is possible. The light source is filtered according D65, C and UV ex level.



RYCOLAB

Applicable Standards

- ISO 2469, ISO 2470, ISO 3688, ISO 11475, ISO 11476, TAPPI T 519, TAPPI T 525, TAPPI T 527

Specifications

- Measurements: Color, Color difference, Absolute and Delta values, E for CIE XYZ, xyz, L*, a*, b*, C*, h*, u* v*, CIE, Opacity, Fluorescence, etc...
- Illumination/viewing system:
Reflectance:
0° (diffuse illumination, 0° viewing)
- Light-Receiving element:
Silicone photodiode array
(dual 40 elements)
- Spectral separation device:
Diffraction grating
- Wavelength range: 360 – 740 nm
- Wavelength pitch: 10 nm
- Reflectance range:
0 – 200%, resolution: 0.01%
- Light source: 3 x pulsed xenon lamps
- Measurement time: 1.5 seconds for measurements of fluorescent colors, 9600 bps
- Measurement area: Ø 30 mm
- Illumination area: Ø 34 mm

Thwing-Albert Instrument Company

14 W. Collings Avenue, West Berlin, NJ 08091, USA

tel 856-767-1000 ■ fax 856-767-2615 ■ info@thwingalbert.com

www.thwingalbert.com



**An ISO 9001
Registered Company**