

14 Collings Avenue, West Berlin, NJ 08091

## TAS90 Vise Grip 50 kN

### Ordering information:

The grips are ordered in pairs but can also be ordered separately (0.5 pair). Grips and jaws need to be ordered separately.

We recommend the usage of an air screwdriver.







Item number	TAS90
Tensile force	50 kN
Temperature range	0°C - +180°C Other temperature ranges on request
Body	Steel, manganese phosphate coating
Weight	12 kg each grip (without jaws)
Scope of delivery	1 pair of grips

Jaws for TAS90: Scope of delivery: 1 set = 4 jaws

Item No.	Surface	Clamping surface H x W	Opening	Weight per pair
TAS90-B	Blank (smooth) jaws	60 x 66 mm	0 – 30 mm	1.2 kg
TAS90-BP	Pyramid jaws (serrated)	60 x 66 mm	0 – 30 mm	1.1 kg
TAS90-BV	V-jaws	60 x 66 mm	5 – 30 mm Ø	1.1 kg
TAS90-BW	Wave jaws	60 x 66 mm	0 – 30 mm	1.1 kg
TAS90-BD	Diamond jaws	60 x 66 mm	0 – 30 mm	1.1 kg
TAS90-B210	Blank (smooth) jaws	70 x 210 mm	0 – 10 mm	6.6 kg
TAS90-BP210	Pyramid jaws (serrated)	70 x 210 mm	0 – 10 mm	6.6 kg
TAS90-BW210	Wave jaws	70 x 210 mm	0 – 10 mm	6.4 kg

Jaws with other dimensions and surface coatings on request

	<b>Blank jaws</b> <ul style="list-style-type: none"> <li>• Suitable for own further treatments</li> <li>• Steel-blanks without coating</li> </ul>
	<b>Pyramid jaws</b> <ul style="list-style-type: none"> <li>• Pyramids 1.2x45°</li> <li>• Hardened steel 58HRC manganese phosphated</li> </ul>
	<b>V-jaws</b> <ul style="list-style-type: none"> <li>• For all kinds of round samples</li> <li>• Tooth pitch 1.2 mm</li> <li>• Hardened steel 58HRC manganese phosphated</li> </ul>
	<b>Wave jaws</b> <ul style="list-style-type: none"> <li>• For flexible materials</li> <li>• Wave 5 mm</li> <li>• Hardened steel 58HRC manganese phosphated</li> </ul>
	<b>Diamond jaws</b> <ul style="list-style-type: none"> <li>• Clamping surface coated with synthetic diamonds</li> <li>• Nickel-plated</li> </ul>

