## Vibramax Package Shaker VMX-1100

The VMX-1100 is a small sized package shaker designed for the laboratory simulation of typical hazards present in distribution environment.

Its rigid platform with adjustable restraining fences moves in a 25.4 mm peak to peak vertical sinusoidal motion and applies a uniform vibration input over the entire test specimen.

The vibration frequency is linearly adjustable within the range of 2-5Hz and 120-300 rpm so the user can test a package under its exact resonance frequency. The test evaluates destructive performance in minimal test periods.

This equipment enables the assessment of external and internal packaging. The VMX-1100 has a rugged machine design that ensures reliable operation with minimal maintenance.

The VMX-1100 has a remote control panel for comfortable and safe operation. There is an optional 750  $\times$  750 mm test platform can be supplied upon request.

**Optional Accessories:** Special custom made restraining fences

Maximum Capacity: 75 kg

Test Platform Size: 750 x 750 mm

Double Amplitude Test Displacement: 25.4 mm

Adjustable Test Frequency: 2-5 Hz

Industry Standards: ISO 2247/B & ASTM D999/A1





## SPECIFICATIONS

- Power Supply: 220 VAC, 50 / 60 Hz, 1.25 kW, single phase
- Dimensions (W x L x H):

Base: 834 x 656 x 536 mm

Panel: 200 x 300 x 400 mm

Weight: 155 kg





thwingalbert.com